

Sinteso™ S-LINE

FDOOTC241

Multi-sensor fire detector



Multi-sensor fire detector with ASAtechnology™ to evaluate the three criteria smoke, heat, and CO

- Signal processing with **ASAtechnology** (Advanced Signal Analysis)
- Event-controlled detection behavior
- Quick response to all fires that generate carbon monoxide (CO)
- Early and reliable detection when fires occur
- High immunity in environments with deceptive phenomena
- Suitable for wind speeds of 1...20 m/s
- Separate detection of toxic CO
- Prepared for future requirements thanks to its configurability
- Communication via FDnet

Features

- Resistant to environmental and interfering influences such as dust, fibers, insects, moisture, extreme temperatures, electromagnetic interference, corrosive vapors, vibration, artificial aerosols, and atypical fire phenomena
- Shock resistant, theft protection as an accessory
- Signal processing with **ASAtechnology**
- Time and process-dependent detection behavior
- High degree of immunity to faults in power electronics
- Protected electronics, high-quality components
- Sophisticated sensors and electronic monitoring
- Redundant, high-quality sensor system
- Internal alarm indicator (IAI), 360° visibility
- Integrated line separator

Ecological benefits

- Environmentally friendly processing
- Reusable materials
- Electronic parts and synthetic materials can be easily separated
- Environmentally friendly detector-testing without gas

Use

Alongside its fire detection functionality, the FDOOTC241 also has a CO detection functionality.

Multi-sensor fire detector, neural ASA (S-LINE), FDOOTC241



Fire detection function:

- Functions according to the scattered light principle with two sensors, optical forward and backward scattering
- Opto-electronic measuring chamber which obstructs disruptive extraneous light but provides excellent detection of both light and dark smoke particles
- Two additional heat sensors and an additional CO sensor increase the fire detector's response behavior and immunity to deceptive phenomena
- Selectable detection behavior thanks to application-specific ASA parameter sets

CO detection function:

- Functions using an electro-chemical CO cell
- CO concentration alarm is transmitted to an independent technical CO alarm channel ('Technical alarm CO')
- Independent processing of the CO signal for the CO alarm channel and CO signal for fire detection
- Selectable detection behavior of the CO alarm channel, regardless of ASA parameter sets for fire detection

Use:

- Areas with increased CO exposure, e.g., heating rooms, combustion plants, fermentation plants, garages, automotive workshops, animal stalls, chemical laboratories, or production sites
- For early detection of smoldering fires that generate carbon monoxide (CO) (e.g., mattress fires in homes)
- For early and reliable fire detection in an environment with deceptive phenomena
- Can be used addressed

Type Overview

Type	Designation	Order number	Weight [kg]
FDOOTC241	Multi-sensor fire detector, neural ASA (S-LINE)	S54311-F1-A1	0.107
Accessories			
FDB221	Detector base, addressable	A5Q00001664	0.026
FDB221-AA	Detector base, addressable incl. 1 micro terminal DBZ1190-AA	A5Q00012741	0.029
FDB222	Addressable detector base, flat	S54319-F1-A1	0.025

Product documentation

Document ID	Title
008164	Equipment overview Sinteso™ Detector system FD20
008331	List of compatibility (for 'Sinteso™' product line)
A6V10209291	Technical manual Neural fire detector FDOOTC241
007775	Data Sheet Detector bases and accessories FDB22x, FDB20x, FDB241, FDB251, FDB281, FDB299


Related documents such as environmental declarations, CE declarations, etc., can be downloaded at the following Internet address:

<http://siemens.com/bt/download>

Mounting

Mounting options

- Easy, time-saving, and completely reliable mounting
- Base with stilts FDB221, FDB221-AA for surface-mounted and recess-mounted cable entries
- Base without slits FDB222 for flush mounting. For recess-mounted cable entry only
- Extra-long mounting slits allow existing drill holes from other systems to be reused.
- A large opening in the detector base makes it easy to feed the cables through.
- The detector line can be connected without any tools: The wire can be inserted easily by hand through screwless connection terminals (spring clip principle).
- The detector can be screwed into the base easily either manually or using a detector exchanger.
- The alarm indicator (AI) is centered in the detector, which means there is no need to align the detector



1	Detector base	4	Opening for cable entry
2	Screwless connection terminals	5	Point detector FDOOTC241
3	Mounting slits	6	Internal alarm indicator (AI)

Efficiency on-site

- 'One-man' testing, commissioning, diagnostics, and maintenance
- Exchange the detector without resetting the parameters
- Exchange the detector without a ladder at heights up to 8 m

Disposal



The device is considered an electronic device for disposal in accordance with the European Guidelines and may not be disposed of as domestic garbage.


- Dispose of the device through channels provided for this purpose.
- Comply with all local and currently applicable laws and regulations.

Technical data

	FDOOTC241
Operating voltage (modulated)	DC 12...33 V
Operating current (quiescent)	Typ. 320...400 µA
External alarm indicator without sounder base	2
External alarm indicator with sounder base	1
Operating temperature	-20...+50 °C
Storage temperature	-20...+55 °C
Air humidity (short-term moisture condensation permitted)	15...90 % rel.
Communication protocol	FDnet
Color	~RAL 9010 pure white
Protection category (IEC 60529):	
• Base FDB221/FDB222	IP43
• Base attachment FDB291 with base FDB221/FDB222	IP43
• Base attachment wet FDB295 with base FDB221/FDB222 and FDOOTC241	IP44
• Sounder base FDSB29x	IP43
Standards	EN 54-5, EN 54-7, EN 54-17, CEA 4021
Approvals	
• VdS	G209040
• LPCB	126bh/04
• FM	3040250
Permissible wind speed	Max. 20 m/s
System compatibility	FS20

Dimensional drawings

1	2
FDOOTC241 with base FDB221, FDB221-AA for surface-mounted and recess-mounted cable entries	FDOOTC241 with base FDB222 for flush mounting. For recess-mounted cable entry only

09  0786	FDOOTC241	Siemens Schweiz AG; Theilerstrasse 1a CH-6300 Zug Technical data: see doc. A6V10209291
FDOOTC241 - Smoke/heat detector incl. short-circuit isolator for use in fire detection and fire alarm systems installed in buildings.		
305/2011/EU (CPR): EN 54-5 / EN 54-7 / EN 54-17 ; 2014/30/EU (EMC): EN 50130-4 / EN 61000-6-3 ; 2011/65/EU (RoHS): EN 50581		
The declared performance and conformity can be seen in the Declaration of Performance (DoP) and the EU Declaration of Conformity (DoC), which is obtainable via the Customer Support Center: Tel. +49 89 9221-8000 or https://siemens.com/bt/download		
DoP No.: 0786-CPR-20694; DoC No.: CED-FDOOTC241		

Issued by
 Siemens Switzerland Ltd
 Building Technologies Division
 International Headquarters
 Theilerstrasse 1a
 CH-6300 Zug
 Tel. +41 58 724 2424
www.siemens.com/buildingtechnologies

© Siemens Switzerland Ltd, 2008
 Technical specifications and availability subject to change without notice.