



## *Environmental Product Declaration*

<b>Product</b>	Type of equipment	<b>Operating unit</b>	
	Designation	<b>FCM2030-C2</b>	
	Product line	<b>FS20</b>	
<b>Process control</b>	Siemens Switzerland Ltd Building Technologies Group Gubelstrasse 22 CH-6301 Zug		
	Management system certified	since	by
	ISO 14001 (environment)	<b>06.12.2002</b>	<b>Gerling Cert</b>
	ISO 9001 (quality)	<b>06.11.1989</b>	<b>SQS/VdS</b>
<b>Environmentally compatible product design</b>	Product responsibility of Siemens covers the entire product life cycle. Siemens already assess, avoids and minimizes the environmental impact of its products with respect to production, procurement, sales, use, services and disposal during the product and process planning phases by complying Siemens Standard SN 36350 "Environmentally compatible products".		
<b>Product use</b>	Typical energy consumption per year	<b>22 kWh/a</b>	
	Maintenance	<b>Not necessary</b>	
<b>Risk of fire</b>	Fire load	<b>35.1 MJ</b>	
<b>Packaging</b>	20-PAP Corrugated fiber board	<b>Packaging operating unit</b>	<b>370 g</b>
	20-PAP Corrugated fiber board	<b>Folding box to op. unit</b>	<b>132 g</b>
	20-PAP Corrugated fiber board	<b>Corrugated fiber board</b>	<b>260 g</b>
	Polyester, polyethylene	<b>Static shielding bag</b>	<b>23 g</b>
	PE	<b>Plastic bag</b>	<b>20 g</b>
	Notes on disposal	<b>One-way, recyclable</b>	

<b>Materials</b>		Total weight of device	<b>2568 g</b>
Plastics	ABS+PC, halogenated	FHA2011-A2 cover cap	<b>645 g</b>
	Q Silicone rubber, halogenated	FCM2012-A1 Keypad	<b>239 g</b>
	Q Silicone rubber, halogenated	FTO2004-C1 Keypad	<b>55 g</b>
	PVC rigid, halogenated	Flat cable mounting	<b>6 g</b>
	PA6	Switching lever	<b>3 g</b>
	Polyester foil	Design foil	<b>41 g</b>
Metals	Steel, zinc plated	FCM2010-A1 support op. Unit	<b>935 g</b>
	Steel, zinc plated	Screws	<b>30 g</b>
	Steel, zinc plated	Lock carrier to Z3S200	<b>3 g</b>
	Brass, nickel plated	KABA-cheese	<b>72 g</b>
	Brass, nickel plated	Key	<b>21 g</b>
	Brass, nickel plated	Clip to KABA-cheese SM 22MM	<b>3 g</b>
	CrNi steel	Shielding plate PMI	<b>47 g</b>
	Others	PBT GF, Be/Cu, PVC	20pol. Cable
PBT GF, Be/Cu, PVC		34pol. Cable	<b>38 g</b>
PCB assembled	FR4, TBBA, SnAgCu	FCM2027 PMI- & Mainboard	<b>358 g</b>
	FR4, TBBA, SnAgCu	PCB cpl. FTO2004-C1 FBA terminal	<b>48 g</b>
	FR4, TBBA, SnAgCu	FCC2006-A1 CPU Modul	<b>18 g</b>

The total weight of a device may deviate from the total of the weights of all individual components due to rounding.

## Disposal



The device is classified as waste electronic equipment in terms of the European Directive 2002/96/EC (WEEE) and should not be disposed of as unsorted municipal waste. The relevant national legal rules are to be adhered to. Regarding disposal, use the systems setup for collecting electronic waste.

Observe all local and applicable laws.

## Comments

### Environmental Benefits:

- Servers for the early detection of fires and prevents the discharge of toxic gases.
- Easily removable. Disassembling is possible without any important effects regarding waste disposal.

#### Legal disclaimer: This declaration is for information purposes only

This Environmental Product Declaration does not constitute a guarantee of the composition of a product, neither does it guarantee that the product will retain a particular composition for a particular period. Siemens Switzerland Ltd therefore does not assume liability for any error or for any consequences which may arise from the use of this information to the maximum extent under the law.

Please contact your local Siemens branch office to get further information on environmental aspects and disposal.