





# Supplementary Protectors

## 5SX2, N-type 55 mm mounting depth

### Features

The 5SX2 has been approved acc. to UL 1077 and CSA 22.2 No. 235-M 89 and can therefore be used as "supplementary protectors" for applications of up to 277 V AC (1-pole design) and 480 V AC (2-pole and 3-pole design).

### Selection and ordering data

	$I_n$	MW	Characteristic A <sup>1)</sup>		Characteristic B		Characteristic C		Characteristic D		Weight 1 item kg	Pack. unit Items
			Order No.	Price 1 item	Order No.	Price 1 item	Order No.	Price 1 item	Order No.	Price 1 item		
 <p><b>1-pole</b></p> 	0.3	1	-	-	-	5SX2 114-7 <sup>1)</sup>	-	-	0.140	12		
	0.5		-	-	-	5SX2 105-7	5SX2 105-8					
	1		5SX2 101-5	-	-	5SX2 101-7	5SX2 101-8					
	1.6		5SX2 115-5	-	-	5SX2 115-7	5SX2 115-8					
	2		5SX2 102-5	-	-	5SX2 102-7	5SX2 102-8					
	3		5SX2 103-5	-	-	5SX2 103-7	5SX2 103-8					
	4		5SX2 104-5	-	-	5SX2 104-7	5SX2 104-8					
	5		-	-	-	5SX2 111-7	-					
	6		5SX2 106-5	5SX2 106-6	5SX2 106-6	5SX2 106-7	5SX2 106-8					
	8		-	-	-	5SX2 108-7	5SX2 108-8					
	10		5SX2 110-5	5SX2 110-6	5SX2 110-6	5SX2 110-7	5SX2 110-8					
	13		-	5SX2 113-6	5SX2 113-6	5SX2 113-7	5SX2 113-8					
	15		-	-	-	5SX2 118-7	-					
	16		5SX2 116-5	5SX2 116-6	5SX2 116-6	5SX2 116-7	5SX2 116-8					
	20		5SX2 120-5	5SX2 120-6	5SX2 120-6	5SX2 120-7	5SX2 120-8					
	25		5SX2 125-5	5SX2 125-6	5SX2 125-6	5SX2 125-7	5SX2 125-8					
30		-	-	-	5SX2 130-7	-						
32		5SX2 132-5	5SX2 132-6	5SX2 132-6	5SX2 132-7	5SX2 132-8						
40		5SX2 140-5	5SX2 140-6	5SX2 140-6	5SX2 140-7	5SX2 140-8 <sup>1)</sup>	0.115					
50		-	5SX2 150-6	5SX2 150-6	5SX2 150-7	5SX2 150-8 <sup>1)</sup>						
63		-	-	-	5SX2 163-7 <sup>1)</sup>	-	0.150					
 <p><b>2-pole</b></p> 	0.5	2	-	-	-	5SX2 205-7	5SX2 205-8	0.280	6			
	1		5SX2 201-5	-	-	5SX2 201-7	5SX2 201-8					
	1.6		5SX2 215-5	-	-	5SX2 215-7	5SX2 215-8					
	2		5SX2 202-5	-	-	5SX2 202-7	5SX2 202-8					
	3		5SX2 203-5	-	-	5SX2 203-7	5SX2 203-8					
	4		5SX2 204-5	-	-	5SX2 204-7	5SX2 204-8					
	5		-	-	-	5SX2 211-7	-					
	6		5SX2 206-5	5SX2 206-6	5SX2 206-6	5SX2 206-7	5SX2 206-8					
	8		-	-	-	5SX2 208-7	5SX2 208-8					
	10		5SX2 210-5	5SX2 210-6	5SX2 210-6	5SX2 210-7	5SX2 210-8					
	13		-	5SX2 213-6	5SX2 213-6	5SX2 213-7	5SX2 213-8					
	15		-	-	-	5SX2 218-7	-					
	16		5SX2 216-5	5SX2 216-6	5SX2 216-6	5SX2 216-7	5SX2 216-8					
	20		5SX2 220-5	5SX2 220-6	5SX2 220-6	5SX2 220-7	5SX2 220-8					
	25		5SX2 225-5	5SX2 225-6	5SX2 225-6	5SX2 225-7	5SX2 225-8					
	30		-	-	-	5SX2 230-7	-					
32		5SX2 232-5	5SX2 232-6	5SX2 232-6	5SX2 232-7	5SX2 232-8						
40		5SX2 240-5	5SX2 240-6	5SX2 240-6	5SX2 240-7	5SX2 240-8 <sup>1)</sup>	0.300					
50		-	5SX2 250-6	5SX2 250-6	5SX2 250-7	5SX2 250-8 <sup>1)</sup>						
63		-	-	-	5SX2 263-7 <sup>1)</sup>	-						

1) Without UL 1077 or CSA 22.2 No. 235-M 89



1 MW = modular width of 18 mm  
N-type = device mounting depth of 55 mm

## 5SX2, N-type, 6kA 55 mm mounting depth

### Features

The 5SX2 has been approved acc. to UL 1077 and CSA 22.2 No. 235-M 89 and can therefore be used as "supplementary protectors" for applications of up to 277 V AC (1-pole design) and 480 V AC (2-pole and 3-pole design).

### Selection and ordering data

	$I_n$	MW	Characteristic A <sup>1)</sup>		Characteristic B		Characteristic C		Characteristic D		Weight Pack.	
			Order No.	Price 1 item	Order No.	Price 1 item	Order No.	Price 1 item	Order No.	Price 1 item	kg	Items
 <p><b>3-pole</b></p> 	0.5	3	-	-	-	5SX2 305-7	5SX2 305-8	0.440	4			
	1		5SX2 301-5	-	-	5SX2 301-7	5SX2 301-8					
	1.6		5SX2 315-5	-	-	5SX2 315-7	5SX2 315-8					
	2		5SX2 302-5	-	-	5SX2 302-7	5SX2 302-8					
	3		5SX2 303-5	-	-	5SX2 303-7	5SX2 303-8					
	4		5SX2 304-5	-	-	5SX2 304-7	5SX2 304-8					
	5		-	-	-	5SX2 311-7	-					
	6		5SX2 306-5	5SX2 306-6	5SX2 306-6	5SX2 306-7	5SX2 306-8					
	8		-	-	-	5SX2 308-7	5SX2 308-8					
	10		5SX2 310-5	5SX2 310-6	5SX2 310-6	5SX2 310-7	5SX2 310-8					
	13		-	5SX2 313-6	5SX2 313-6	5SX2 313-7	5SX2 313-8					
	15		-	-	-	5SX2 318-7	-					
	16		5SX2 316-5	5SX2 316-6	5SX2 316-6	5SX2 316-7	5SX2 316-8					
	20		5SX2 320-5	5SX2 320-6	5SX2 320-6	5SX2 320-7	5SX2 320-8					
	25		5SX2 325-5	5SX2 325-6	5SX2 325-6	5SX2 325-7	5SX2 325-8					
	30		-	-	-	5SX2 330-7	-					
32		5SX2 332-5	5SX2 332-6	5SX2 332-6	5SX2 332-7	5SX2 332-8						
40		5SX2 340-5	5SX2 340-6	5SX2 340-6	5SX2 340-7	5SX2 340-8 <sup>1)</sup>	5SX2 340-8 <sup>1)</sup>	0.450				
50		-	5SX2 350-6	5SX2 350-6	5SX2 350-7	5SX2 350-8 <sup>1)</sup>	5SX2 350-8 <sup>1)</sup>					
63		-	-	-	5SX2 363-7 <sup>1)</sup>	-						

1) Without UL 1077 or CSA 22.2 No. 235-M 89

1 MW = modular width of 18 mm  
N-type = device mounting depth of 55 mm