Proprietary data, company confidential. All rights reserved
Confie a titre de secret d'entreprise. Tous droits reserves
Communicado como segredo empresarial. Reservados todos os direitos.
Confiado como secreto industrial. Nos reservamos todos los derechos.

Weitergabe sowie Vervielfaeltigung dieser Unterlage, Verwertung und Mitteilung ihres Inhaltes nicht gestattet, soweit nicht ausdrueklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte fuer den Fall der Patenterteilung oder GM-Eintragung vorbehalten.

Die Zeichnung wurde mit Pro/Engineer erstellt

NOTES
1) TERMINALS RECOMMENDED ARE PRE-INSULATED & MUST BE CRIMPED USING APPROVED TOOLING.
AMP PIDG OR PLASTI GRIP FUNNEL ENTRY (RING TONGUE) FOR M4 FIXING STUD.

SUPPLIER	PART NUMBER	CABLE SIZE
AMP	342103	0.25-1.6mm²
AMP	342143	1.0-2.6mm²

OR ANY OTHER MANUFACTURERS EQUIVALENT TERMINAL.

2) FOR OUTLINE & PANEL DRILLING, SEE 2995X10004 (A4).

3) CONNECTIONS TO THIS COMMUNICATIONS FACILITY IS BY SCREENED, TWISTED PAIR CABLE, ON SITE.
WHEN WIRING OTHER FACILITIES ENSURE THAT THESE TERMINALS ARE NOT OBSCURED BY OTHER WIRE RUNS.

4) CONTACTS SHOWN THUS 
ARE INTERNAL RELAY CASE ASSEMBLY CONTACTS AND CLOSE WHEN THE RELAY CHASSIS IS WITHDRAWN FROM THE CASE.

5) FOR THE RELAY CASE ASSEMBLY SEE 2436G40046

ABBREVIATIONS
I-CURRENT INPUTS
BI-BINARY INPUTS
BO-BINARY OUTPUTS
CO-CHANGE OVER BINARY OUTPUT CONTACTS
NO-NORMALLY OPEN BINARY OUTPUT CONTACTS
NC-NORMALLY CLOSED BINARY OUTPUT CONTACTS

COMMUNICATIONS IDENTIFICATION	
COM1	RS485 (ON BLOCK 'B' TERMINALS 14,16,18 & 20)
COM2	USB TYPE 'B' PORT (ON RELAY FRONT LABEL)
COM3	ETHERNET(x2) PORTS (ON REAR COMMS MODULE)







FOR INTERNAL USE ONLY
UNCONTROLLED COPY
NOT SUBJECT TO UPDATE

UNSPECIFIED TOLERANCES (IN MM)	
DIMENSION	TOLERANCE
0 < 6	±0.1
6 < 15	±0.15
15 < 30	±0.2
30 <	±0.25

Rev.	Change	Date	Name
1A	DRAWING RELEASED	25042017	AMAR

FINISH
Maßstab/Scale NTS
Volumen[cm^3]:
Material:

	Name	Date
DRN. BY	AMAR	25042017
CHD. BY	JOHN SP.	25042017
APPD. BY	JAYANT J.	25042017

EM EA PRO R&D

Title
TERMINAL ID & WIRING DIAGRAM FOR 7SR17
4CT+3BI+5BO(2CO+3NO), OPTICAL ETH(x2),8 RTD

Siemens Ltd

Document No 2436W40054
Rev. 1A
7SR17
Sheet 1 of 1