



MODULE LABEL KEY

ANALOGUE MODULE	AN 1 etc
INPUT/OUTPUT MODULE	I/O 1 etc
P.S.U. & BASIC I/O MODULE	P.S.U.

ABBREVIATIONS

CT-CURRENT INPUTS
VT-VOLTAGE INPUTS
SI-STATUS INPUTS
CO-CHANGE OVER OUTPUT CONTACTS
NO-NORMALLY OPEN OUTPUT CONTACTS
NC-NORMALLY CLOSED OUTPUT CONTACTS

FOR INFORMATION ONLY  
UNCONTROLLED COPY  
NOT SUBJECT TO UPDATE

MATERIAL:

Dimensions in millimetres ; Surface texture in micrometres.  
Machine where marked ✓  
For explanation of dimensions, tolerances, notes etc. see B.S.308.  
Limit on untoleranced unmachined dimensions ±  
Limits on untoleranced machined dimensions to B.S.4500;  
i.e. up to 6±0.1; over 30 to 120±0.3; over 315±0.8;  
over 6 to 30±0.2; over 120 to 315±0.5;  
General unmachined angular tolerance ±

Finish:	Title:	First used on:
Treatment:	TERM IDENT & WIRING DIAGRAM FOR IOTA RELAY (59SI,3C0,42NO) E16 CASE	Similar Articles:
	VA TECH Reyrolle AUTOMATION, CONTROL & PROTECTION	Supersedes:
	Original Scale: NTS	Drg. No. 2761W11029

Copyright © 2005 VA TECH Reyrolle Ltd. Hebburn

1	13/07/05	CHANGE
ISSUE	DATE	NOTED

DRAWN RDW | CHECKED RDW | APPROVED RD.WATSON | DATE 13/07/05 | IE | OPS | PCP | Purch.Spec. | TQ | EAC | CE | STD | A1