

SIPROTEC

I/O-Box 6MD61

Communication module

PROFIBUS-DP
Bus mapping

Preface

Table of contents

Data of the PROFIBUS-DP messages	1
Standard mapping 3-1	2
Standard mapping 3-2	3
Standard mapping 3-3	4
Standard mapping 3-4	5
Standard mapping 3-5	6
Standard mapping 3-6	7

Index

Revision 1.00.01

Edition: September 2005

C53000-L2140-A319-1

Liability statement

We have checked the contents of this manual against the hardware and software described. Exclusions and deviations cannot be ruled out; we accept no liability for lack of total agreement.

The information in this manual is checked periodically, and necessary corrections will be included in future editions.

We appreciate any suggested improvements.

We reserve the right to make technical improvements without notice.

Copyright

Copyright © Siemens AG 2005. All rights reserved.

Dissemination or reproduction of this document, or evaluation and communication of its contents, is not authorized except where expressly permitted. Violations are liable for damages. All rights reserved, particularly for the purposes of patent application or trademark registration.

Registered trademarks

SIPROTEC®, SIMATIC®, SIMATIC NET®, SINAUT®, SICAM® and DIGSI® are registered trademarks of Siemens AG.

Other designations in this manual may be trademarks that if used by third parties for their own purposes may violate the rights of the owner.

Preface

Purpose of this manual

This manual describes the data in the PROFIBUS-DP messages of the SIPROTEC device 6MD61 and is divided into the following topics:

- Data of the PROFIBUS-DP messages → Chapter 1,
- Standard mapping 3-1 → Chapter 2,
- Standard mapping 3-2 → Chapter 3,
- Standard mapping 3-3 → Chapter 4,
- Standard mapping 3-4 → Chapter 5,
- Standard mapping 3-5 → Chapter 6,
- Standard mapping 3-6 → Chapter 7.

General details about the function, operation, assembly and commissioning of the SIPROTEC devices you find in the

- SIPROTEC4 System Manual, order no. E50417–H1176–C151.

PROFIBUS-DP communication profile documentation

The following additional manual informs you about the data types, bus specific parameters and hardware interface of the PROFIBUS-DP slave module of the SIPROTEC devices:

Manual	Order number
SIPROTEC Communication module, PROFIBUS-DP - Communication profile	C53000-L1840-B001-03

PROFIBUS-DP specification

The PROFIBUS-DP specification and the structure of the PROFIBUS-DP messages are defined in the European Standard EN 50170:

- PROFIBUS Specification
Normative Parts of PROFIBUS-FMS, -DP, -PA
According to the European Standard
EN 50170, Volume 2
PROFIBUS Nutzerorganisation e.V.

Validity

This manual is valid for the SIPROTEC device:

- 6MD61 (firmware version 4.00 or higher)

with

- PROFIBUS-DP communication module version 04.02.02 or higher.



Note:

Only PROFIBUS communication modules from HW-Rev. 4 (ref. to “PROFIBUS-DP communication profile documentation”) may be used with the 6MD61 devices.

For device parameterization have to be used:

- DIGSI 4.60 or higher,
- PROFIBUS-DP standard mappings 3-1 to 3-n
(n = device type dependent number of standard mappings).

Additional Support

For questions regarding SIPROTEC4 devices, please contact your Siemens representative.

Training courses

Individual course offerings may be found in our Training Catalog and questions can be directed to our Training Centre. Please contact your Siemens representative.

Target audience

Protection engineers, commissioning engineers, personnel concerned with adjustment, checking and service of selective protective equipment, automatic and control facilities and personnel of electrical facilities and power plants.



Warning!

Hazardous voltages are present in this electrical equipment during operation. Non-observance of the safety rules can result in severe personal injury or property damage.

Only qualified personnel shall work on and around this equipment after becoming thoroughly familiar with all warnings and safety notices of this and the associated manuals as well as with the applicable safety regulations.

The successful and safe operation of this device is dependent on proper transport and storage, proper handling, installation, operation, and maintenance by qualified personnel under observance of all warnings and hints contained in this and the associated manuals.

In particular the general erection and safety regulations (e.g. IEC, EN, DIN, VDE, or other national and international standards) regarding the correct use of high-voltage installations must be observed. Non-observance can result in death, personal injury or substantial property damage.

QUALIFIED PERSONNEL

For the purpose of this manual and product labels, a qualified person is one who is familiar with the installation, construction and operation of the equipment and the hazards involved. In addition, he has the following qualifications:

- Is trained and authorized to energize, de-energize, clear, ground and tag circuits and equipment in accordance with established safety practices.
- Is trained in the proper care and use of protective equipment in accordance with established safety practices.
- Is trained in rendering first aid.

Typographic and graphical conventions

The following text formats are used to identify concepts giving device information described by the text flow:

Parameter names, or identifiers for configuration or function parameters that appear in the device display or on the screen of a PC (with DIGSI) are shown in mono-script (same point size) bold text. This also applies to header bars for selection menus.

Parameter conditions, or possible settings of parameters that appear in the device display or on the screen of a PC (with DIGSI), are additionally shown in italic style. This also applies to selection items for selection menus.

„Annunciations“, or identifiers for information produced by the device or required by other devices or from the switchgear is shown in mono-script (same point size) and placed into quotation marks.

For diagrams in which the identifier type results from the representation itself, text conventions may differ from the above-mentioned.

Revision index

Listing of the changes between the editions of this manual:

Modified chapters / pages	Edition	Reasons of modification
	1.00.01	First edition, Doc.-No.: C53000-L2140-A319-1 September 9 th , 2005

Table of contents

Preface	3
Revision index	7
1 Data of the PROFIBUS-DP messages	13
1.1 Explanations	14
1.2 Messages in output direction: PROFIBUS-DP master to the SIPROTEC device	16
1.3 Messages in input direction: SIPROTEC device to the PROFIBUS-DP master	17
1.3.1 Annunciations	17
1.3.2 Measured values	17
1.4 Configuration data of the standard mappings.....	18
2 Standard mapping 3-1	23
2.1 Message in output direction.....	24
2.1.1 Double commands.....	24
2.1.2 Single commands	24
2.2 Message in input direction	26
2.2.1 Annunciations	26
2.2.1.1 Double-point indications	26
2.2.1.2 Single-point indications.....	26
2.2.1.3 Diagnosis.....	27
3 Standard mapping 3-2	29
3.1 Message in output direction.....	30
3.1.1 Event list	30
3.1.2 Double commands.....	30
3.1.3 Single commands	30
3.2 Message in input direction	32
3.2.1 Annunciations	32
3.2.1.1 Double-point indications	32
3.2.1.2 Single-point indications.....	32

3.2.1.3	Diagnosis	33
3.2.2	Event list	34
4	Standard mapping 3-3	35
4.1	Message in output direction	36
4.1.1	Double commands	36
4.1.2	Single commands	37
4.2	Message in input direction	39
4.2.1	Annunciations	39
4.2.1.1	Double-point indications	39
4.2.1.2	Single-point indications	40
4.2.1.3	Diagnosis	41
4.2.2	Measured values	42
5	Standard mapping 3-4	43
5.1	Message in output direction	44
5.1.1	Event list	44
5.1.2	Double commands	44
5.1.3	Single commands	45
5.2	Message in input direction	47
5.2.1	Annunciations	47
5.2.1.1	Double-point indications	47
5.2.1.2	Single-point indications	48
5.2.1.3	Diagnosis	49
5.2.2	Measured values	50
5.2.3	Event list	51
6	Standard mapping 3-5	53
6.1	Message in output direction	54
6.1.1	Double commands	54
6.1.2	Single commands	55
6.2	Message in input direction	59
6.2.1	Annunciations	59
6.2.1.1	Double-point indications	59
6.2.1.2	Single-point indications	61
6.2.1.3	Diagnosis	64
7	Standard mapping 3-6	65
7.1	Message in output direction	66
7.1.1	Event list	66
7.1.2	Double commands	66
7.1.3	Single commands	68

7.2	Message in input direction.....	71
7.2.1	Annunciations.....	71
7.2.1.1	Double-point indications.....	71
7.2.1.2	Single-point indications.....	73
7.2.1.3	Diagnosis.....	76
7.2.2	Event list.....	76
Glossary		77
Index		79

Data of the PROFIBUS-DP messages

This chapter delivers explanations to the data descriptions of the standard mapping as well as notes for evaluation of selected SIPROTEC objects and for the configuration of the standard mapping in the PROFIBUS-DP master.

1.1	Explanations	14
1.2	Messages in output direction: PROFIBUS-DP master to the SIPROTEC device	16
1.3	Messages in input direction: SIPROTEC device to the PROFIBUS-DP master	17
1.4	Configuration data of the standard mappings	18

1.1 Explanations



Note:

The examples shown in this chapter 1.1 do not necessarily correspond to the real allocation of the objects in the bus mapping.

Chapters 2 to 7 define the data area of the PROFIBUS-DP messages for data transfer between the PROFIBUS-DP slave of the SIPROTEC devices 6MD61 and the PROFIBUS-DP master.

The columns "Designation of the SIPROTEC objects" contain the names of the SIPROTEC objects for "US English" device language.

The listed SIPROTEC objects in the PROFIBUS-DP messages' data area are sorted after byte offset, beginning with 0.

Variables with data type greater than or equal to 1 byte

The offset defines the start of the most significant byte in the message, e.g.:

Offset	Designation of the SIPROTEC objects	Comments	Scaling (32767 corresponds to...)	Internal object no.
16	Ia =	Current in phase A	3276.7 A	601

The measured value "Ia" is assigned to data byte 16 (most significant byte of the measured value) and data byte 17 (least significant byte of the measured value) in the PROFIBUS-DP message

Bit variables (SP/SC, DP/DC)

The offset indicates the byte which contains the bit value and the position of bit 0 of the bit variable, e.g. (input message):

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	Breaker ON/OFF OFF	Circuit breaker	-
0 / 1	Breaker ON/OFF ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
5 / 5	Error Sum Alarm	1 = Error with a summary alarm ON	140

The checkback signal from the circuit breaker (as double-point indication) is located in data byte 0, bit position 2^0 (bit 0) and 2^1 (bit 1).

The single-point indication "Error Sum Alarm" is located in byte 5, bit position 2^5 .



Note:

In the manual "SIPROTEC Communication module, PROFIBUS-DP - Communication profile" (ref. to page 3) you find:

- Definition of the data types (single-point/double-point indication, measured value etc.),
 - Description of the event list via PROFIBUS-DP (handshake bytes, message blocks etc.),
 - Notes for parameterization in DIGSI.
-

1.2 Messages in output direction: PROFIBUS-DP master to the SIPROTEC device

The messages in PROFIBUS-DP output direction (ref to chap. 2.1, 3.1, 4.1, 5.1, 6.1 and 7.1) allow:

- command outputs through the output relays of the SIPROTEC devices .



Note:

- The allocation of the output relays to the switching devices and to the output channels is defined during parameterization of the SIPROTEC devices.
 - Depending on the device composition there may be less than indicated output relays (and corresponding PROFIBUS-DP message positions) available in the SIPROTEC device.
-

1.3 Messages in input direction: SIPROTEC device to the PROFIBUS-DP master

The messages in PROFIBUS-DP input direction (ref. to chap. 2.2, 3.2, 4.2, 5.2, 6.2 and 7.2) allow:

- polling of binary inputs,
- transmission of measurands to the PROFIBUS-DP master.

1.3.1 Annunciations



Note:

- The allocation of the input channels to the binary inputs is defined during parameterization of the devices.
 - Depending on the device composition and the existing protection packages not all of the indicated binary inputs or protection annunciations (and corresponding PROFIBUS-DP message positions) may be available in the SIPROTEC device.
-

1.3.2 Measured values



Note:

Depending on the device composition not all of the indicated analog inputs (and corresponding PROFIBUS-DP message positions) may be available in the SIPROTEC device.

The given default scaling values for the measured values in the standard mappings apply to installations where the nominal operating values are in the ranges given below:

Full Scale Voltage (parameter address 1101):

→ 1.01 ... 100.00 kV

Full Scale Current (parameter address 1102):

→ 10.01 ... 1000.00 A



Note:

Changes of the scaling of the measured values are possible in adaption of the concrete installation environment.

You find information about this in the manual "SIPROTEC Communication module, PROFIBUS-DP - Communication profile" (ref. to page 3).

1.4 Configuration data of the standard mappings

There are six standard mappings (standard mapping 3-1 to standard mapping 3-6) available for the SIPROTEC devices 6MD61 which differ in the data size of the PROFIBUS-DP messages.

Standard mappings 3-1 and 3-2

The *standard mappings 3-1 and 3-2* cover the number of binary inputs and relay outputs for the SIPROTEC devices 6MD611.

In addition to the standard mapping 3-1, the standard mapping 3-2 contains an event list for transmission of indications with time stamp.

The standard mapping 3-1 contains:

Output direction:

- 4 double commands
- 12 single commands

Input direction:

- 10 double-point indications
- 28 single-point indications

The standard mapping 3-2 contains:

Output direction:

- Handshake byte for event list via PROFIBUS-DP
- 4 double commands
- 12 single commands

Input direction:

- 10 double-point indications
- 28 single-point indications
- Handshake byte and three message blocks for event list via PROFIBUS-DP

Standard mappings 3-3 and 3-4

The *standard mappings 3-3 and 3-4* cover the number of binary inputs and relay outputs for the SIPROTEC devices 6MD612.

In addition to the standard mapping 3-3, the standard mapping 3-4 contains an event list for transmission of indications with time stamp.

The standard mapping 3-3 contains:

Output direction:

- 10 double commands
- 22 single commands

Input direction:

- 16 double-point indications
- 48 single-point indications
- 9 measured values (integer)

The standard mapping 3-4 contains:

Output direction:

- Handshake byte for event list via PROFIBUS-DP
- 10 double commands
- 22 single commands

Input direction:

- 16 double-point indications
- 48 single-point indications
- 9 measured values (integer)
- Handshake byte and three message blocks for event list via PROFIBUS-DP

**Standard mappings
3-5 and 3-6**

The *standard mappings 3-5 and 3-6* cover the number of binary inputs and relay outputs for the SIPROTEC devices 6MD613.

In addition to the standard mapping 3-5, the standard mapping 3-6 contains an event list for transmission of indications with time stamp.

The standard mapping 3-5 contains:

Output direction:

- 26 double commands
- 54 single commands

Input direction:

- 42 double-point indications
- 92 single-point indications

The standard mapping 3-6 contains:

Output direction:

- Handshake byte for event list via PROFIBUS-DP
- 26 double commands
- 54 single commands

Input direction:

- 42 double-point indications
- 92 single-point indications
- Handshake byte and three message blocks for event list via PROFIBUS-DP

**PROFIBUS-DP
Configuration data**

- Standard mapping 3-1:* **15H 23H**
(6 bytes input-, 4 bytes output direction)
- Standard mapping 3-2:* **15H DFH 25H**
(38 bytes input-, 6 bytes output direction)
- Standard mapping 3-3:* **1FH 1BH 27H**
(28 bytes input-, 8 bytes output direction)
- Standard mapping 3-4:* **1FH 1BH DFH 29H**
(60 bytes input-, 10 bytes output direction)
- Standard mapping 3-5:* **1FH 15H 2FH 23H**
(22 bytes input-, 20 bytes output direction)
- Standard mapping 3-6:* **1FH 15H DFH 2FH 25H**
(54 bytes input-, 22 bytes output direction)

**PROFIBUS-DP
master**

At the configuration of a PROFIBUS-DP slave of the SIPROTEC devices in the parameterization system of the PROFIBUS-DP master are to select the following modules for the 6MD61 standard mappings and to allocate associated addresses in the I/O addressing range of the PROFIBUS-DP master:

Standard mapping 3-1:

Module	Order number	Input address	Output address
0	Input - 6 Bytes	Adr_lx	
1	Output - 4 Bytes		Adr_Ox

Standard mapping 3-2:

Module	Order number	Input address	Output address
0	Input - 6 Bytes	Adr_lx	
1	Input - 16 Words, consistent	Adr_lx + 6	
2	Output - 6 Bytes		Adr_Ox

Standard mapping 3-3:

Module	Order number	Input address	Output address
0	Input - 16 Bytes	Adr_lx	
1	Input - 12 Bytes	Adr_lx + 16	
2	Output - 8 Bytes		Adr_Ox

Standard mapping 3-4:

Module	Order number	Input address	Output address
0	Input - 16 Bytes	Adr_lx	
1	Input - 12 Bytes	Adr_lx + 16	
2	Input - 16 Words, consistent	Adr_lx + 28	
3	Output - 10 Bytes		Adr_Ox

Standard mapping 3-5:

Module	Order number	Input address	Output address
0	Input - 16 Bytes	Adr_lx	
1	Input - 6 Bytes	Adr_lx + 16	
2	Output - 16 Bytes		Adr_Ox
3	Output - 4 Bytes		Adr_Ox + 16

Standard mapping 3-6:

Module	Order number	Input address	Output address
0	Input - 16 Bytes	Adr_lx	
1	Input - 6 Bytes	Adr_lx + 16	
2	Input - 16 Words, consistent	Adr_lx + 22	
3	Output - 16 Bytes		Adr_Ox
4	Output - 6 Bytes		Adr_Ox + 16

Adr_lx and Adr_Ox indicate arbitrary (as a rule even) addresses in the I/O addressing range of the PROFIBUS-DP master.

Adr_lx (base address of the inputs) is identical with offset 0 of the PROFIBUS-DP message data of the SIPROTEC device in input direction (ref. to chap. 2.2, 3.2, 4.2, 5.2, 6.2 and 7.2).

Adr_Ox (base address of the outputs) is identical with offset 0 of the PROFIBUS-DP message data of the SIPROTEC device in output direction (ref. to chap. 2.1, 3.1, 4.1, 5.1, 6.1 and 7.1).

Standard mapping 3-1

This chapter describes the data in the PROFIBUS-DP messages between the PROFIBUS-DP master and the SIPROTEC devices 6MD61 if standard mapping 3-1 is selected.

2.1	Message in output direction	24
2.2	Message in input direction	26

2.1 Message in output direction

2.1.1 Double commands

- Double commands with double-point indications as checkback indication can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		

2.1.2 Single commands

- Single commands can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		

2.2 Message in input direction

2.2.1 Annunciations

2.2.1.1 Double-point indications

- Double-point indications (e.g. checkback indications of double commands) can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		

2.2.1.2 Single-point indications

- Single-point indications can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
2 / 4	<user-defined>	not pre-allocated	-
2 / 5	<user-defined>	not pre-allocated	-

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
2 / 6	<user-defined>	not pre-allocated	-
2 / 7	<user-defined>	not pre-allocated	-
3 / 0	<user-defined>	not pre-allocated	-
3 / 1	<user-defined>	not pre-allocated	-
3 / 2	<user-defined>	not pre-allocated	-
3 / 3	<user-defined>	not pre-allocated	-
3 / 4	<user-defined>	not pre-allocated	-
3 / 5	<user-defined>	not pre-allocated	-
3 / 6	<user-defined>	not pre-allocated	-
3 / 7	<user-defined>	not pre-allocated	-
4 / 0	<user-defined>	not pre-allocated	-
4 / 1	<user-defined>	not pre-allocated	-
4 / 2	<user-defined>	not pre-allocated	-
4 / 3	<user-defined>	not pre-allocated	-
4 / 4	<user-defined>	not pre-allocated	-
4 / 5	<user-defined>	not pre-allocated	-
4 / 6	<user-defined>	not pre-allocated	-
4 / 7	<user-defined>	not pre-allocated	-
5 / 0	<user-defined>	not pre-allocated	-
5 / 1	<user-defined>	not pre-allocated	-
5 / 2	<user-defined>	not pre-allocated	-

2.2.1.3 Diagnosis

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
5 / 3	Device OK	1 = Update of the device replica in the SIPROTEC device completed after initial start or restart	51
5 / 4	Settings Calc.	1 = Settings calculation is running	70
5 / 5	Error Sum Alarm	1 = Error with a summary alarm ON	140
5 / 6	Alarm Sum Event	1 = Alarm summary event ON	160
5 / 7	Data valid	1 = Data in the PROFIBUS-DP message are valid. (This indication is created by the PROFIBUS-DP slave; not available in DIGSI and not relocatable.)	-

Standard mapping 3-2

This chapter describes the data in the PROFIBUS-DP messages between the PROFIBUS-DP master and the SIPROTEC devices 6MD61 if standard mapping 3-2 is selected.

3.1	Message in output direction	30
3.2	Message in input direction	32

3.1 Message in output direction

3.1.1 Event list

- Information regarding the handshake bytes as well as the retrieval methods of the event list via PROFIBUS-DP can be found in the manual "SIPROTEC Communication module, PROFIBUS-DP - Communication profile".

Offset	Designation	Comments	Internal object no.
0	Control_O	Handshake byte for event list via PROFIBUS-DP	-
1	SPARE	reserved for future use (the value at this position is ignored)	-

3.1.2 Double commands

- Double commands with double-point indications as checkback indication can be routed on these positions as "Source system interface" using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		

3.1.3 Single commands

- Single commands can be routed on these positions as "Source system interface" using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		
4 / 0	<user-defined> OFF	not pre-allocated	-
4 / 1	<user-defined> ON		
4 / 2	<user-defined> OFF	not pre-allocated	-
4 / 3	<user-defined> ON		
4 / 4	<user-defined> OFF	not pre-allocated	-
4 / 5	<user-defined> ON		
4 / 6	<user-defined> OFF	not pre-allocated	-
4 / 7	<user-defined> ON		
5 / 0	<user-defined> OFF	not pre-allocated	-
5 / 1	<user-defined> ON		
5 / 2	<user-defined> OFF	not pre-allocated	-
5 / 3	<user-defined> ON		
5 / 4	<user-defined> OFF	not pre-allocated	-
5 / 5	<user-defined> ON		
5 / 6	<user-defined> OFF	not pre-allocated	-
5 / 7	<user-defined> ON		

3.2 Message in input direction

3.2.1 Annunciations

3.2.1.1 Double-point indications

- Double-point indications (e.g. checkback indications of double commands) can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		

3.2.1.2 Single-point indications

- Single-point indications can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
2 / 4	<user-defined>	not pre-allocated	-
2 / 5	<user-defined>	not pre-allocated	-

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
2 / 6	<user-defined>	not pre-allocated	-
2 / 7	<user-defined>	not pre-allocated	-
3 / 0	<user-defined>	not pre-allocated	-
3 / 1	<user-defined>	not pre-allocated	-
3 / 2	<user-defined>	not pre-allocated	-
3 / 3	<user-defined>	not pre-allocated	-
3 / 4	<user-defined>	not pre-allocated	-
3 / 5	<user-defined>	not pre-allocated	-
3 / 6	<user-defined>	not pre-allocated	-
3 / 7	<user-defined>	not pre-allocated	-
4 / 0	<user-defined>	not pre-allocated	-
4 / 1	<user-defined>	not pre-allocated	-
4 / 2	<user-defined>	not pre-allocated	-
4 / 3	<user-defined>	not pre-allocated	-
4 / 4	<user-defined>	not pre-allocated	-
4 / 5	<user-defined>	not pre-allocated	-
4 / 6	<user-defined>	not pre-allocated	-
4 / 7	<user-defined>	not pre-allocated	-
5 / 0	<user-defined>	not pre-allocated	-
5 / 1	<user-defined>	not pre-allocated	-
5 / 2	<user-defined>	not pre-allocated	-

3.2.1.3 Diagnosis

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
5 / 3	Device OK	1 = Update of the device replica in the SIPROTEC device completed after initial start or restart	51
5 / 4	Settings Calc.	1 = Settings calculation is running	70
5 / 5	Error Sum Alarm	1 = Error with a summary alarm ON	140
5 / 6	Alarm Sum Event	1 = Alarm summary event ON	160
5 / 7	Data valid	1 = Data in the PROFIBUS-DP message are valid. (This indication is created by the PROFIBUS-DP slave; not available in DIGSI and not relocatable.)	-

3.2.2 Event list

- Information regarding the handshake bytes as well as the retrieval methods of the event list via PROFIBUS-DP can be found in the manual “SIPROTEC Communication module, PROFIBUS-DP - Communication profile”.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
6	Control_I	Handshake byte for event list via PROFIBUS-DP	-
7	SPARE	reserved for future use (the value 0 is transmitted at this position)	-
8	Message block #1	Identification #1	-
9		Value #1	
10 - 17		Time stamp #1	
18	Message block #2	Identification #2	-
19		Value #2	
20 - 27		Time stamp #2	
28	Message block #3	Identification #3	-
29		Value #3	
30 - 37		Time stamp #3	

Standard mapping 3-3

This chapter describes the data in the PROFIBUS-DP messages between the PROFIBUS-DP master and the SIPROTEC devices 6MD61 if standard mapping 3-3 is selected.

4.1	Message in output direction	36
4.2	Message in input direction	39

4.1 Message in output direction

4.1.1 Double commands

- Double commands with double-point indications as checkback indication can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		

4.1.2 Single commands

- Single commands can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		
4 / 0	<user-defined> OFF	not pre-allocated	-
4 / 1	<user-defined> ON		
4 / 2	<user-defined> OFF	not pre-allocated	-
4 / 3	<user-defined> ON		
4 / 4	<user-defined> OFF	not pre-allocated	-
4 / 5	<user-defined> ON		
4 / 6	<user-defined> OFF	not pre-allocated	-
4 / 7	<user-defined> ON		
5 / 0	<user-defined> OFF	not pre-allocated	-
5 / 1	<user-defined> ON		
5 / 2	<user-defined> OFF	not pre-allocated	-
5 / 3	<user-defined> ON		
5 / 4	<user-defined> OFF	not pre-allocated	-
5 / 5	<user-defined> ON		
5 / 6	<user-defined> OFF	not pre-allocated	-
5 / 7	<user-defined> ON		
6 / 0	<user-defined> OFF	not pre-allocated	-
6 / 1	<user-defined> ON		
6 / 2	<user-defined> OFF	not pre-allocated	-
6 / 3	<user-defined> ON		
6 / 4	<user-defined> OFF	not pre-allocated	-
6 / 5	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
6 / 6	<user-defined> OFF	not pre-allocated	-
6 / 7	<user-defined> ON		
7 / 0	<user-defined> OFF	not pre-allocated	-
7 / 1	<user-defined> ON		
7 / 2	<user-defined> OFF	not pre-allocated	-
7 / 3	<user-defined> ON		
7 / 4	<user-defined> OFF	not pre-allocated	-
7 / 5	<user-defined> ON		
7 / 6	<user-defined> OFF	not pre-allocated	-
7 / 7	<user-defined> ON		

4.2 Message in input direction

4.2.1 Annunciations

4.2.1.1 Double-point indications

- Double-point indications (e.g. checkback indications of double commands) can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		

4.2.1.2 Single-point indications

- Single-point indications can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
4 / 0	<user-defined>	not pre-allocated	-
4 / 1	<user-defined>	not pre-allocated	-
4 / 2	<user-defined>	not pre-allocated	-
4 / 3	<user-defined>	not pre-allocated	-
4 / 4	<user-defined>	not pre-allocated	-
4 / 5	<user-defined>	not pre-allocated	-
4 / 6	<user-defined>	not pre-allocated	-
4 / 7	<user-defined>	not pre-allocated	-
5 / 0	<user-defined>	not pre-allocated	-
5 / 1	<user-defined>	not pre-allocated	-
5 / 2	<user-defined>	not pre-allocated	-
5 / 3	<user-defined>	not pre-allocated	-
5 / 4	<user-defined>	not pre-allocated	-
5 / 5	<user-defined>	not pre-allocated	-
5 / 6	<user-defined>	not pre-allocated	-
5 / 7	<user-defined>	not pre-allocated	-
6 / 0	<user-defined>	not pre-allocated	-
6 / 1	<user-defined>	not pre-allocated	-
6 / 2	<user-defined>	not pre-allocated	-
6 / 3	<user-defined>	not pre-allocated	-
6 / 4	<user-defined>	not pre-allocated	-
6 / 5	<user-defined>	not pre-allocated	-
6 / 6	<user-defined>	not pre-allocated	-
6 / 7	<user-defined>	not pre-allocated	-
7 / 0	<user-defined>	not pre-allocated	-
7 / 1	<user-defined>	not pre-allocated	-
7 / 2	<user-defined>	not pre-allocated	-

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
7 / 3	<user-defined>	not pre-allocated	-
7 / 4	<user-defined>	not pre-allocated	-
7 / 5	<user-defined>	not pre-allocated	-
7 / 6	<user-defined>	not pre-allocated	-
7 / 7	<user-defined>	not pre-allocated	-
8 / 0	<user-defined>	not pre-allocated	-
8 / 1	<user-defined>	not pre-allocated	-
8 / 2	<user-defined>	not pre-allocated	-
8 / 3	<user-defined>	not pre-allocated	-
8 / 4	<user-defined>	not pre-allocated	-
8 / 5	<user-defined>	not pre-allocated	-
8 / 6	<user-defined>	not pre-allocated	-
8 / 7	<user-defined>	not pre-allocated	-
9 / 0	<user-defined>	not pre-allocated	-
9 / 1	<user-defined>	not pre-allocated	-
9 / 2	<user-defined>	not pre-allocated	-

4.2.1.3 Diagnosis

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
9 / 3	Device OK	1 = Update of the device replica in the SIPROTEC device completed after initial start or restart	51
9 / 4	Settings Calc.	1 = Settings calculation is running	70
9 / 5	Error Sum Alarm	1 = Error with a summary alarm ON	140
9 / 6	Alarm Sum Event	1 = Alarm summary event ON	160
9 / 7	Data valid	1 = Data in the PROFIBUS-DP message are valid. (This indication is created by the PROFIBUS-DP slave; not available in DIGSI and not relocatable.)	-

4.2.2 Measured values

- Ref. to chap.1.3.2 for additional notes regarding scaling of measured values.

Offset	Designation of the SIPROTEC objects	Comments	Scaling (32767 corresponds to ...)	Internal object no.
10	Va =	Va	327.67 kV	621
12	Vb =	Vb	327.67 kV	622
14	Vc =	Vc	327.67 kV	623
16	Ia =	Ia	3276.7 A	601
18	Ib =	Ib	3276.7 A	602
20	Ic =	Ic	3276.7 A	603
22	In =	In	3276.7 A	604
24	Td1=	Transducer 1 (0...20 mA)	327.67 mA	996
26	Td2 =	Transducer 2 (0...20 mA)	327.67 mA	997

Standard mapping 3-4

This chapter describes the data in the PROFIBUS-DP messages between the PROFIBUS-DP master and the SIPROTEC devices 6MD61 if standard mapping 3-4 is selected.

5.1	Message in output direction	44
5.2	Message in input direction	47

5.1 Message in output direction

5.1.1 Event list

- Information regarding the handshake bytes as well as the retrieval methods of the event list via PROFIBUS-DP can be found in the manual “SIPROTEC Communication module, PROFIBUS-DP - Communication profile”.

Offset	Designation	Comments	Internal object no.
0	Control_O	Handshake byte for event list via PROFIBUS-DP	-
1	SPARE	reserved for future use (the value at this position is ignored)	-

5.1.2 Double commands

- Double commands with double-point indications as checkback indication can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		
4 / 0	<user-defined> OFF	not pre-allocated	-
4 / 1	<user-defined> ON		
4 / 2	<user-defined> OFF	not pre-allocated	-
4 / 3	<user-defined> ON		

5.1.3 Single commands

- Single commands can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
4 / 4	<user-defined> OFF	not pre-allocated	-
4 / 5	<user-defined> ON		
4 / 6	<user-defined> OFF	not pre-allocated	-
4 / 7	<user-defined> ON		
5 / 0	<user-defined> OFF	not pre-allocated	-
5 / 1	<user-defined> ON		
5 / 2	<user-defined> OFF	not pre-allocated	-
5 / 3	<user-defined> ON		
5 / 4	<user-defined> OFF	not pre-allocated	-
5 / 5	<user-defined> ON		
5 / 6	<user-defined> OFF	not pre-allocated	-
5 / 7	<user-defined> ON		
6 / 0	<user-defined> OFF	not pre-allocated	-
6 / 1	<user-defined> ON		
6 / 2	<user-defined> OFF	not pre-allocated	-
6 / 3	<user-defined> ON		
6 / 4	<user-defined> OFF	not pre-allocated	-
6 / 5	<user-defined> ON		
6 / 6	<user-defined> OFF	not pre-allocated	-
6 / 7	<user-defined> ON		
7 / 0	<user-defined> OFF	not pre-allocated	-
7 / 1	<user-defined> ON		
7 / 2	<user-defined> OFF	not pre-allocated	-
7 / 3	<user-defined> ON		
7 / 4	<user-defined> OFF	not pre-allocated	-
7 / 5	<user-defined> ON		
7 / 6	<user-defined> OFF	not pre-allocated	-
7 / 7	<user-defined> ON		
8 / 0	<user-defined> OFF	not pre-allocated	-
8 / 1	<user-defined> ON		
8 / 2	<user-defined> OFF	not pre-allocated	-
8 / 3	<user-defined> ON		
8 / 4	<user-defined> OFF	not pre-allocated	-
8 / 5	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
8 / 6	<user-defined> OFF	not pre-allocated	-
8 / 7	<user-defined> ON		
9 / 0	<user-defined> OFF	not pre-allocated	-
9 / 1	<user-defined> ON		
9 / 2	<user-defined> OFF	not pre-allocated	-
9 / 3	<user-defined> ON		
9 / 4	<user-defined> OFF	not pre-allocated	-
9 / 5	<user-defined> ON		
9 / 6	<user-defined> OFF	not pre-allocated	-
9 / 7	<user-defined> ON		

5.2 Message in input direction

5.2.1 Annunciations

5.2.1.1 Double-point indications

- Double-point indications (e.g. checkback indications of double commands) can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		

5.2.1.2 Single-point indications

- Single-point indications can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
4 / 0	<user-defined>	not pre-allocated	-
4 / 1	<user-defined>	not pre-allocated	-
4 / 2	<user-defined>	not pre-allocated	-
4 / 3	<user-defined>	not pre-allocated	-
4 / 4	<user-defined>	not pre-allocated	-
4 / 5	<user-defined>	not pre-allocated	-
4 / 6	<user-defined>	not pre-allocated	-
4 / 7	<user-defined>	not pre-allocated	-
5 / 0	<user-defined>	not pre-allocated	-
5 / 1	<user-defined>	not pre-allocated	-
5 / 2	<user-defined>	not pre-allocated	-
5 / 3	<user-defined>	not pre-allocated	-
5 / 4	<user-defined>	not pre-allocated	-
5 / 5	<user-defined>	not pre-allocated	-
5 / 6	<user-defined>	not pre-allocated	-
5 / 7	<user-defined>	not pre-allocated	-
6 / 0	<user-defined>	not pre-allocated	-
6 / 1	<user-defined>	not pre-allocated	-
6 / 2	<user-defined>	not pre-allocated	-
6 / 3	<user-defined>	not pre-allocated	-
6 / 4	<user-defined>	not pre-allocated	-
6 / 5	<user-defined>	not pre-allocated	-
6 / 6	<user-defined>	not pre-allocated	-
6 / 7	<user-defined>	not pre-allocated	-
7 / 0	<user-defined>	not pre-allocated	-
7 / 1	<user-defined>	not pre-allocated	-
7 / 2	<user-defined>	not pre-allocated	-

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
7 / 3	<user-defined>	not pre-allocated	-
7 / 4	<user-defined>	not pre-allocated	-
7 / 5	<user-defined>	not pre-allocated	-
7 / 6	<user-defined>	not pre-allocated	-
7 / 7	<user-defined>	not pre-allocated	-
8 / 0	<user-defined>	not pre-allocated	-
8 / 1	<user-defined>	not pre-allocated	-
8 / 2	<user-defined>	not pre-allocated	-
8 / 3	<user-defined>	not pre-allocated	-
8 / 4	<user-defined>	not pre-allocated	-
8 / 5	<user-defined>	not pre-allocated	-
8 / 6	<user-defined>	not pre-allocated	-
8 / 7	<user-defined>	not pre-allocated	-
9 / 0	<user-defined>	not pre-allocated	-
9 / 1	<user-defined>	not pre-allocated	-
9 / 2	<user-defined>	not pre-allocated	-

5.2.1.3 Diagnosis

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
9 / 3	Device OK	1 = Update of the device replica in the SIPROTEC device completed after initial start or restart	51
9 / 4	Settings Calc.	1 = Settings calculation is running	70
9 / 5	Error Sum Alarm	1 = Error with a summary alarm ON	140
9 / 6	Alarm Sum Event	1 = Alarm summary event ON	160
9 / 7	Data valid	1 = Data in the PROFIBUS-DP message are valid. (This indication is created by the PROFIBUS-DP slave; not available in DIGSI and not relocatable.)	-

5.2.2 Measured values

- Ref. to chap.1.3.2 for additional notes regarding scaling of measured values.

Offset	Designation of the SIPROTEC objects	Comments	Scaling (32767 corresponds to ...)	Internal object no.
10	Va =	Va	327.67 kV	621
12	Vb =	Vb	327.67 kV	622
14	Vc =	Vc	327.67 kV	623
16	Ia =	Ia	3276.7 A	601
18	Ib =	Ib	3276.7 A	602
20	Ic =	Ic	3276.7 A	603
22	In =	In	3276.7 A	604
24	Td1=	Transducer 1 (0...20 mA)	327.67 mA	996
26	Td2 =	Transducer 2 (0...20 mA)	327.67 mA	997

5.2.3 Event list

- Information regarding the handshake bytes as well as the retrieval methods of the event list via PROFIBUS-DP can be found in the manual "SIPROTEC Communication module, PROFIBUS-DP - Communication profile".

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
27	Control_I	Handshake byte for event list via PROFIBUS-DP	-
28	SPARE	reserved for future use (the value 0 is transmitted at this position)	-
29	Message block #1	Identification #1	-
30		Value #1	
31		Time stamp #1	
- 39			
40	Message block #2	Identification #2	-
41		Value #2	
42		Time stamp #2	
- 49			
50	Message block #3	Identification #3	-
51		Value #3	
52		Time stamp #3	
- 59			

Standard mapping 3-5

This chapter describes the data in the PROFIBUS-DP messages between the PROFIBUS-DP master and the SIPROTEC devices 6MD61 if standard mapping 3-5 is selected.

6.1	Message in output direction	54
6.2	Message in input direction	59

6.1 Message in output direction

6.1.1 Double commands

- Double commands with double-point indications as checkback indication can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		
4 / 0	<user-defined> OFF	not pre-allocated	-
4 / 1	<user-defined> ON		
4 / 2	<user-defined> OFF	not pre-allocated	-
4 / 3	<user-defined> ON		
4 / 4	<user-defined> OFF	not pre-allocated	-
4 / 5	<user-defined> ON		
4 / 6	<user-defined> OFF	not pre-allocated	-
4 / 7	<user-defined> ON		
5 / 0	<user-defined> OFF	not pre-allocated	-
5 / 1	<user-defined> ON		
5 / 2	<user-defined> OFF	not pre-allocated	-
5 / 3	<user-defined> ON		
5 / 4	<user-defined> OFF	not pre-allocated	-
5 / 5	<user-defined> ON		
5 / 6	<user-defined> OFF	not pre-allocated	-
5 / 7	<user-defined> ON		
6 / 0	<user-defined> OFF	not pre-allocated	-
6 / 1	<user-defined> ON		
6 / 2	<user-defined> OFF	not pre-allocated	-
6 / 3	<user-defined> ON		

6.1.2 Single commands

- Single commands can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
6 / 4	<user-defined> OFF	not pre-allocated	-
6 / 5	<user-defined> ON		
6 / 6	<user-defined> OFF	not pre-allocated	-
6 / 7	<user-defined> ON		
7 / 0	<user-defined> OFF	not pre-allocated	-
7 / 1	<user-defined> ON		
7 / 2	<user-defined> OFF	not pre-allocated	-
7 / 3	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
7 / 4	<user-defined> OFF	not pre-allocated	-
7 / 5	<user-defined> ON		
7 / 6	<user-defined> OFF	not pre-allocated	-
7 / 7	<user-defined> ON		
8 / 0	<user-defined> OFF	not pre-allocated	-
8 / 1	<user-defined> ON		
8 / 2	<user-defined> OFF	not pre-allocated	-
8 / 3	<user-defined> ON		
8 / 4	<user-defined> OFF	not pre-allocated	-
8 / 5	<user-defined> ON		
8 / 6	<user-defined> OFF	not pre-allocated	-
8 / 7	<user-defined> ON		
9 / 0	<user-defined> OFF	not pre-allocated	-
9 / 1	<user-defined> ON		
9 / 2	<user-defined> OFF	not pre-allocated	-
9 / 3	<user-defined> ON		
9 / 4	<user-defined> OFF	not pre-allocated	-
9 / 5	<user-defined> ON		
9 / 6	<user-defined> OFF	not pre-allocated	-
9 / 7	<user-defined> ON		
10 / 0	<user-defined> OFF	not pre-allocated	-
10 / 1	<user-defined> ON		
10 / 2	<user-defined> OFF	not pre-allocated	-
10 / 3	<user-defined> ON		
10 / 4	<user-defined> OFF	not pre-allocated	-
10 / 5	<user-defined> ON		
10 / 6	<user-defined> OFF	not pre-allocated	-
10 / 7	<user-defined> ON		
11 / 0	<user-defined> OFF	not pre-allocated	-
11 / 1	<user-defined> ON		
11 / 2	<user-defined> OFF	not pre-allocated	-
11 / 3	<user-defined> ON		
11 / 4	<user-defined> OFF	not pre-allocated	-
11 / 5	<user-defined> ON		
11 / 6	<user-defined> OFF	not pre-allocated	-
11 / 7	<user-defined> ON		
12 / 0	<user-defined> OFF	not pre-allocated	-
12 / 1	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
12 / 2	<user-defined> OFF	not pre-allocated	-
12 / 3	<user-defined> ON		
12 / 4	<user-defined> OFF	not pre-allocated	-
12 / 5	<user-defined> ON		
12 / 6	<user-defined> OFF	not pre-allocated	-
12 / 7	<user-defined> ON		
13 / 0	<user-defined> OFF	not pre-allocated	-
13 / 1	<user-defined> ON		
13 / 2	<user-defined> OFF	not pre-allocated	-
13 / 3	<user-defined> ON		
13 / 4	<user-defined> OFF	not pre-allocated	-
13 / 5	<user-defined> ON		
13 / 6	<user-defined> OFF	not pre-allocated	-
13 / 7	<user-defined> ON		
14 / 0	<user-defined> OFF	not pre-allocated	-
14 / 1	<user-defined> ON		
14 / 2	<user-defined> OFF	not pre-allocated	-
14 / 3	<user-defined> ON		
14 / 4	<user-defined> OFF	not pre-allocated	-
14 / 5	<user-defined> ON		
14 / 6	<user-defined> OFF	not pre-allocated	-
14 / 7	<user-defined> ON		
15 / 0	<user-defined> OFF	not pre-allocated	-
15 / 1	<user-defined> ON		
15 / 2	<user-defined> OFF	not pre-allocated	-
15 / 3	<user-defined> ON		
15 / 4	<user-defined> OFF	not pre-allocated	-
15 / 5	<user-defined> ON		
15 / 6	<user-defined> OFF	not pre-allocated	-
15 / 7	<user-defined> ON		
16 / 0	<user-defined> OFF	not pre-allocated	-
16 / 1	<user-defined> ON		
16 / 2	<user-defined> OFF	not pre-allocated	-
16 / 3	<user-defined> ON		
16 / 4	<user-defined> OFF	not pre-allocated	-
16 / 5	<user-defined> ON		
16 / 6	<user-defined> OFF	not pre-allocated	-
16 / 7	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
17 / 0	<user-defined> OFF	not pre-allocated	-
17 / 1	<user-defined> ON		
17 / 2	<user-defined> OFF	not pre-allocated	-
17 / 3	<user-defined> ON		
17 / 4	<user-defined> OFF	not pre-allocated	-
17 / 5	<user-defined> ON		
17 / 6	<user-defined> OFF	not pre-allocated	-
17 / 7	<user-defined> ON		
18 / 0	<user-defined> OFF	not pre-allocated	-
18 / 1	<user-defined> ON		
18 / 2	<user-defined> OFF	not pre-allocated	-
18 / 3	<user-defined> ON		
18 / 4	<user-defined> OFF	not pre-allocated	-
18 / 5	<user-defined> ON		
18 / 6	<user-defined> OFF	not pre-allocated	-
18 / 7	<user-defined> ON		
19 / 0	<user-defined> OFF	not pre-allocated	-
19 / 1	<user-defined> ON		
19 / 2	<user-defined> OFF	not pre-allocated	-
19 / 3	<user-defined> ON		
19 / 4	<user-defined> OFF	not pre-allocated	-
19 / 5	<user-defined> ON		
19 / 6	<user-defined> OFF	not pre-allocated	-
19 / 7	<user-defined> ON		

6.2 Message in input direction

6.2.1 Annunciations

6.2.1.1 Double-point indications

- Double-point indications (e.g. checkback indications of double commands) can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		
4 / 0	<user-defined> OFF	not pre-allocated	-
4 / 1	<user-defined> ON		
4 / 2	<user-defined> OFF	not pre-allocated	-
4 / 3	<user-defined> ON		
4 / 4	<user-defined> OFF	not pre-allocated	-
4 / 5	<user-defined> ON		
4 / 6	<user-defined> OFF	not pre-allocated	-
4 / 7	<user-defined> ON		
5 / 0	<user-defined> OFF	not pre-allocated	-
5 / 1	<user-defined> ON		
5 / 2	<user-defined> OFF	not pre-allocated	-
5 / 3	<user-defined> ON		
5 / 4	<user-defined> OFF	not pre-allocated	-
5 / 5	<user-defined> ON		
5 / 6	<user-defined> OFF	not pre-allocated	-
5 / 7	<user-defined> ON		
6 / 0	<user-defined> OFF	not pre-allocated	-
6 / 1	<user-defined> ON		
6 / 2	<user-defined> OFF	not pre-allocated	-
6 / 3	<user-defined> ON		
6 / 4	<user-defined> OFF	not pre-allocated	-
6 / 5	<user-defined> ON		
6 / 6	<user-defined> OFF	not pre-allocated	-
6 / 7	<user-defined> ON		
7 / 0	<user-defined> OFF	not pre-allocated	-
7 / 1	<user-defined> ON		
7 / 2	<user-defined> OFF	not pre-allocated	-
7 / 3	<user-defined> ON		
7 / 4	<user-defined> OFF	not pre-allocated	-
7 / 5	<user-defined> ON		
7 / 6	<user-defined> OFF	not pre-allocated	-
7 / 7	<user-defined> ON		
8 / 0	<user-defined> OFF	not pre-allocated	-
8 / 1	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
8 / 2	<user-defined> OFF	not pre-allocated	-
8 / 3	<user-defined> ON		
8 / 4	<user-defined> OFF	not pre-allocated	-
8 / 5	<user-defined> ON		
8 / 6	<user-defined> OFF	not pre-allocated	-
8 / 7	<user-defined> ON		
9 / 0	<user-defined> OFF	not pre-allocated	-
9 / 1	<user-defined> ON		
9 / 2	<user-defined> OFF	not pre-allocated	-
9 / 3	<user-defined> ON		
9 / 4	<user-defined> OFF	not pre-allocated	-
9 / 5	<user-defined> ON		
9 / 6	<user-defined> OFF	not pre-allocated	-
9 / 7	<user-defined> ON		
10 / 0	<user-defined> OFF	not pre-allocated	-
10 / 1	<user-defined> ON		
10 / 2	<user-defined> OFF	not pre-allocated	-
10 / 3	<user-defined> ON		

6.2.1.2 Single-point indications

- Single-point indications can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
10 / 4	<user-defined>	not pre-allocated	-
10 / 5	<user-defined>	not pre-allocated	-
10 / 6	<user-defined>	not pre-allocated	-
10 / 7	<user-defined>	not pre-allocated	-
11 / 0	<user-defined>	not pre-allocated	-
11 / 1	<user-defined>	not pre-allocated	-
11 / 2	<user-defined>	not pre-allocated	-
11 / 3	<user-defined>	not pre-allocated	-
11 / 4	<user-defined>	not pre-allocated	-
11 / 5	<user-defined>	not pre-allocated	-
11 / 6	<user-defined>	not pre-allocated	-
11 / 7	<user-defined>	not pre-allocated	-
12 / 0	<user-defined>	not pre-allocated	-

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
12 / 1	<user-defined>	not pre-allocated	-
12 / 2	<user-defined>	not pre-allocated	-
12 / 3	<user-defined>	not pre-allocated	-
12 / 4	<user-defined>	not pre-allocated	-
12 / 5	<user-defined>	not pre-allocated	-
12 / 6	<user-defined>	not pre-allocated	-
12 / 7	<user-defined>	not pre-allocated	-
13 / 0	<user-defined>	not pre-allocated	-
13 / 1	<user-defined>	not pre-allocated	-
13 / 2	<user-defined>	not pre-allocated	-
13 / 3	<user-defined>	not pre-allocated	-
13 / 4	<user-defined>	not pre-allocated	-
13 / 5	<user-defined>	not pre-allocated	-
13 / 6	<user-defined>	not pre-allocated	-
13 / 7	<user-defined>	not pre-allocated	-
14 / 0	<user-defined>	not pre-allocated	-
14 / 1	<user-defined>	not pre-allocated	-
14 / 2	<user-defined>	not pre-allocated	-
14 / 3	<user-defined>	not pre-allocated	-
14 / 4	<user-defined>	not pre-allocated	-
14 / 5	<user-defined>	not pre-allocated	-
14 / 6	<user-defined>	not pre-allocated	-
14 / 7	<user-defined>	not pre-allocated	-
15 / 0	<user-defined>	not pre-allocated	-
15 / 1	<user-defined>	not pre-allocated	-
15 / 2	<user-defined>	not pre-allocated	-
15 / 3	<user-defined>	not pre-allocated	-
15 / 4	<user-defined>	not pre-allocated	-
15 / 5	<user-defined>	not pre-allocated	-
15 / 6	<user-defined>	not pre-allocated	-
15 / 7	<user-defined>	not pre-allocated	-
16 / 0	<user-defined>	not pre-allocated	-
16 / 1	<user-defined>	not pre-allocated	-
16 / 2	<user-defined>	not pre-allocated	-
16 / 3	<user-defined>	not pre-allocated	-
16 / 4	<user-defined>	not pre-allocated	-
16 / 5	<user-defined>	not pre-allocated	-
16 / 6	<user-defined>	not pre-allocated	-

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
16 / 7	<user-defined>	not pre-allocated	-
17 / 0	<user-defined>	not pre-allocated	-
17 / 1	<user-defined>	not pre-allocated	-
17 / 2	<user-defined>	not pre-allocated	-
17 / 3	<user-defined>	not pre-allocated	-
17 / 4	<user-defined>	not pre-allocated	-
17 / 5	<user-defined>	not pre-allocated	-
17 / 6	<user-defined>	not pre-allocated	-
17 / 7	<user-defined>	not pre-allocated	-
18 / 0	<user-defined>	not pre-allocated	-
18 / 1	<user-defined>	not pre-allocated	-
18 / 2	<user-defined>	not pre-allocated	-
18 / 3	<user-defined>	not pre-allocated	-
18 / 4	<user-defined>	not pre-allocated	-
18 / 5	<user-defined>	not pre-allocated	-
18 / 6	<user-defined>	not pre-allocated	-
18 / 7	<user-defined>	not pre-allocated	-
19 / 0	<user-defined>	not pre-allocated	-
19 / 1	<user-defined>	not pre-allocated	-
19 / 2	<user-defined>	not pre-allocated	-
19 / 3	<user-defined>	not pre-allocated	-
19 / 4	<user-defined>	not pre-allocated	-
19 / 5	<user-defined>	not pre-allocated	-
19 / 6	<user-defined>	not pre-allocated	-
19 / 7	<user-defined>	not pre-allocated	-
20 / 0	<user-defined>	not pre-allocated	-
20 / 1	<user-defined>	not pre-allocated	-
20 / 2	<user-defined>	not pre-allocated	-
20 / 3	<user-defined>	not pre-allocated	-
20 / 4	<user-defined>	not pre-allocated	-
20 / 5	<user-defined>	not pre-allocated	-
20 / 6	<user-defined>	not pre-allocated	-
20 / 7	<user-defined>	not pre-allocated	-
21 / 0	<user-defined>	not pre-allocated	-
21 / 1	<user-defined>	not pre-allocated	-
21 / 2	<user-defined>	not pre-allocated	-

6.2.1.3 Diagnosis

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
21 / 3	Device OK	1 = Update of the device replica in the SIPROTEC device completed after initial start or restart	51
21 / 4	Settings Calc.	1 = Settings calculation is running	70
21 / 5	Error Sum Alarm	1 = Error with a summary alarm ON	140
21 / 6	Alarm Sum Event	1 = Alarm summary event ON	160
21 / 7	Data valid	1 = Data in the PROFIBUS-DP message are valid. (This indication is created by the PROFIBUS-DP slave; not available in DIGSI and not relocatable.)	-

Standard mapping 3-6

This chapter describes the data in the PROFIBUS-DP messages between the PROFIBUS-DP master and the SIPROTEC devices 6MD61 if standard mapping 3-6 is selected.

7.1	Message in output direction	66
7.2	Message in input direction	71

7.1 Message in output direction

7.1.1 Event list

- Information regarding the handshake bytes as well as the retrieval methods of the event list via PROFIBUS-DP can be found in the manual "SIPROTEC Communication module, PROFIBUS-DP - Communication profile".

Offset	Designation	Comments	Internal object no.
0	Control_O	Handshake byte for event list via PROFIBUS-DP	-
1	SPARE	reserved for future use (the value at this position is ignored)	-

7.1.2 Double commands

- Double commands with double-point indications as checkback indication can be routed on these positions as "Source system interface" using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		
4 / 0	<user-defined> OFF	not pre-allocated	-
4 / 1	<user-defined> ON		
4 / 2	<user-defined> OFF	not pre-allocated	-
4 / 3	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
4 / 4	<user-defined> OFF	not pre-allocated	-
4 / 5	<user-defined> ON		
4 / 6	<user-defined> OFF	not pre-allocated	-
4 / 7	<user-defined> ON		
5 / 0	<user-defined> OFF	not pre-allocated	-
5 / 1	<user-defined> ON		
5 / 2	<user-defined> OFF	not pre-allocated	-
5 / 3	<user-defined> ON		
5 / 4	<user-defined> OFF	not pre-allocated	-
5 / 5	<user-defined> ON		
5 / 6	<user-defined> OFF	not pre-allocated	-
5 / 7	<user-defined> ON		
6 / 0	<user-defined> OFF	not pre-allocated	-
6 / 1	<user-defined> ON		
6 / 2	<user-defined> OFF	not pre-allocated	-
6 / 3	<user-defined> ON		
6 / 4	<user-defined> OFF	not pre-allocated	-
6 / 5	<user-defined> ON		
6 / 6	<user-defined> OFF	not pre-allocated	-
6 / 7	<user-defined> ON		
7 / 0	<user-defined> OFF	not pre-allocated	-
7 / 1	<user-defined> ON		
7 / 2	<user-defined> OFF	not pre-allocated	-
7 / 3	<user-defined> ON		
7 / 4	<user-defined> OFF	not pre-allocated	-
7 / 5	<user-defined> ON		
7 / 6	<user-defined> OFF	not pre-allocated	-
7 / 7	<user-defined> ON		
8 / 0	<user-defined> OFF	not pre-allocated	-
8 / 1	<user-defined> ON		
8 / 2	<user-defined> OFF	not pre-allocated	-
8 / 3	<user-defined> ON		

7.1.3 Single commands

- Single commands can be routed on these positions as “Source system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
8 / 4	<user-defined> OFF	not pre-allocated	-
8 / 5	<user-defined> ON		
8 / 6	<user-defined> OFF	not pre-allocated	-
8 / 7	<user-defined> ON		
9 / 0	<user-defined> OFF	not pre-allocated	-
9 / 1	<user-defined> ON		
9 / 2	<user-defined> OFF	not pre-allocated	-
9 / 3	<user-defined> ON		
9 / 4	<user-defined> OFF	not pre-allocated	-
9 / 5	<user-defined> ON		
9 / 6	<user-defined> OFF	not pre-allocated	-
9 / 7	<user-defined> ON		
10 / 0	<user-defined> OFF	not pre-allocated	-
10 / 1	<user-defined> ON		
10 / 2	<user-defined> OFF	not pre-allocated	-
10 / 3	<user-defined> ON		
10 / 4	<user-defined> OFF	not pre-allocated	-
10 / 5	<user-defined> ON		
10 / 6	<user-defined> OFF	not pre-allocated	-
10 / 7	<user-defined> ON		
11 / 0	<user-defined> OFF	not pre-allocated	-
11 / 1	<user-defined> ON		
11 / 2	<user-defined> OFF	not pre-allocated	-
11 / 3	<user-defined> ON		
11 / 4	<user-defined> OFF	not pre-allocated	-
11 / 5	<user-defined> ON		
11 / 6	<user-defined> OFF	not pre-allocated	-
11 / 7	<user-defined> ON		
12 / 0	<user-defined> OFF	not pre-allocated	-
12 / 1	<user-defined> ON		
12 / 2	<user-defined> OFF	not pre-allocated	-
12 / 3	<user-defined> ON		
12 / 4	<user-defined> OFF	not pre-allocated	-
12 / 5	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
12 / 6	<user-defined> OFF	not pre-allocated	-
12 / 7	<user-defined> ON		
13 / 0	<user-defined> OFF	not pre-allocated	-
13 / 1	<user-defined> ON		
13 / 2	<user-defined> OFF	not pre-allocated	-
13 / 3	<user-defined> ON		
13 / 4	<user-defined> OFF	not pre-allocated	-
13 / 5	<user-defined> ON		
13 / 6	<user-defined> OFF	not pre-allocated	-
13 / 7	<user-defined> ON		
14 / 0	<user-defined> OFF	not pre-allocated	-
14 / 1	<user-defined> ON		
14 / 2	<user-defined> OFF	not pre-allocated	-
14 / 3	<user-defined> ON		
14 / 4	<user-defined> OFF	not pre-allocated	-
14 / 5	<user-defined> ON		
14 / 6	<user-defined> OFF	not pre-allocated	-
14 / 7	<user-defined> ON		
15 / 0	<user-defined> OFF	not pre-allocated	-
15 / 1	<user-defined> ON		
15 / 2	<user-defined> OFF	not pre-allocated	-
15 / 3	<user-defined> ON		
15 / 4	<user-defined> OFF	not pre-allocated	-
15 / 5	<user-defined> ON		
15 / 6	<user-defined> OFF	not pre-allocated	-
15 / 7	<user-defined> ON		
16 / 0	<user-defined> OFF	not pre-allocated	-
16 / 1	<user-defined> ON		
16 / 2	<user-defined> OFF	not pre-allocated	-
16 / 3	<user-defined> ON		
16 / 4	<user-defined> OFF	not pre-allocated	-
16 / 5	<user-defined> ON		
16 / 6	<user-defined> OFF	not pre-allocated	-
16 / 7	<user-defined> ON		
17 / 0	<user-defined> OFF	not pre-allocated	-
17 / 1	<user-defined> ON		
17 / 2	<user-defined> OFF	not pre-allocated	-
17 / 3	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
17 / 4	<user-defined> OFF	not pre-allocated	-
17 / 5	<user-defined> ON		
17 / 6	<user-defined> OFF	not pre-allocated	-
17 / 7	<user-defined> ON		
18 / 0	<user-defined> OFF	not pre-allocated	-
18 / 1	<user-defined> ON		
18 / 2	<user-defined> OFF	not pre-allocated	-
18 / 3	<user-defined> ON		
18 / 4	<user-defined> OFF	not pre-allocated	-
18 / 5	<user-defined> ON		
18 / 6	<user-defined> OFF	not pre-allocated	-
18 / 7	<user-defined> ON		
19 / 0	<user-defined> OFF	not pre-allocated	-
19 / 1	<user-defined> ON		
19 / 2	<user-defined> OFF	not pre-allocated	-
19 / 3	<user-defined> ON		
19 / 4	<user-defined> OFF	not pre-allocated	-
19 / 5	<user-defined> ON		
19 / 6	<user-defined> OFF	not pre-allocated	-
19 / 7	<user-defined> ON		
20 / 0	<user-defined> OFF	not pre-allocated	-
20 / 1	<user-defined> ON		
20 / 2	<user-defined> OFF	not pre-allocated	-
20 / 3	<user-defined> ON		
20 / 4	<user-defined> OFF	not pre-allocated	-
20 / 5	<user-defined> ON		
20 / 6	<user-defined> OFF	not pre-allocated	-
20 / 7	<user-defined> ON		
21 / 0	<user-defined> OFF	not pre-allocated	-
21 / 1	<user-defined> ON		
21 / 2	<user-defined> OFF	not pre-allocated	-
21 / 3	<user-defined> ON		
21 / 4	<user-defined> OFF	not pre-allocated	-
21 / 5	<user-defined> ON		
21 / 6	<user-defined> OFF	not pre-allocated	-
21 / 7	<user-defined> ON		

7.2 Message in input direction

7.2.1 Annunciations

7.2.1.1 Double-point indications

- Double-point indications (e.g. checkback indications of double commands) can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
0 / 0	<user-defined> OFF	not pre-allocated	-
0 / 1	<user-defined> ON		
0 / 2	<user-defined> OFF	not pre-allocated	-
0 / 3	<user-defined> ON		
0 / 4	<user-defined> OFF	not pre-allocated	-
0 / 5	<user-defined> ON		
0 / 6	<user-defined> OFF	not pre-allocated	-
0 / 7	<user-defined> ON		
1 / 0	<user-defined> OFF	not pre-allocated	-
1 / 1	<user-defined> ON		
1 / 2	<user-defined> OFF	not pre-allocated	-
1 / 3	<user-defined> ON		
1 / 4	<user-defined> OFF	not pre-allocated	-
1 / 5	<user-defined> ON		
1 / 6	<user-defined> OFF	not pre-allocated	-
1 / 7	<user-defined> ON		
2 / 0	<user-defined> OFF	not pre-allocated	-
2 / 1	<user-defined> ON		
2 / 2	<user-defined> OFF	not pre-allocated	-
2 / 3	<user-defined> ON		
2 / 4	<user-defined> OFF	not pre-allocated	-
2 / 5	<user-defined> ON		
2 / 6	<user-defined> OFF	not pre-allocated	-
2 / 7	<user-defined> ON		
3 / 0	<user-defined> OFF	not pre-allocated	-
3 / 1	<user-defined> ON		
3 / 2	<user-defined> OFF	not pre-allocated	-
3 / 3	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
3 / 4	<user-defined> OFF	not pre-allocated	-
3 / 5	<user-defined> ON		
3 / 6	<user-defined> OFF	not pre-allocated	-
3 / 7	<user-defined> ON		
4 / 0	<user-defined> OFF	not pre-allocated	-
4 / 1	<user-defined> ON		
4 / 2	<user-defined> OFF	not pre-allocated	-
4 / 3	<user-defined> ON		
4 / 4	<user-defined> OFF	not pre-allocated	-
4 / 5	<user-defined> ON		
4 / 6	<user-defined> OFF	not pre-allocated	-
4 / 7	<user-defined> ON		
5 / 0	<user-defined> OFF	not pre-allocated	-
5 / 1	<user-defined> ON		
5 / 2	<user-defined> OFF	not pre-allocated	-
5 / 3	<user-defined> ON		
5 / 4	<user-defined> OFF	not pre-allocated	-
5 / 5	<user-defined> ON		
5 / 6	<user-defined> OFF	not pre-allocated	-
5 / 7	<user-defined> ON		
6 / 0	<user-defined> OFF	not pre-allocated	-
6 / 1	<user-defined> ON		
6 / 2	<user-defined> OFF	not pre-allocated	-
6 / 3	<user-defined> ON		
6 / 4	<user-defined> OFF	not pre-allocated	-
6 / 5	<user-defined> ON		
6 / 6	<user-defined> OFF	not pre-allocated	-
6 / 7	<user-defined> ON		
7 / 0	<user-defined> OFF	not pre-allocated	-
7 / 1	<user-defined> ON		
7 / 2	<user-defined> OFF	not pre-allocated	-
7 / 3	<user-defined> ON		
7 / 4	<user-defined> OFF	not pre-allocated	-
7 / 5	<user-defined> ON		
7 / 6	<user-defined> OFF	not pre-allocated	-
7 / 7	<user-defined> ON		
8 / 0	<user-defined> OFF	not pre-allocated	-
8 / 1	<user-defined> ON		

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
8 / 2	<user-defined> OFF	not pre-allocated	-
8 / 3	<user-defined> ON		
8 / 4	<user-defined> OFF	not pre-allocated	-
8 / 5	<user-defined> ON		
8 / 6	<user-defined> OFF	not pre-allocated	-
8 / 7	<user-defined> ON		
9 / 0	<user-defined> OFF	not pre-allocated	-
9 / 1	<user-defined> ON		
9 / 2	<user-defined> OFF	not pre-allocated	-
9 / 3	<user-defined> ON		
9 / 4	<user-defined> OFF	not pre-allocated	-
9 / 5	<user-defined> ON		
9 / 6	<user-defined> OFF	not pre-allocated	-
9 / 7	<user-defined> ON		
10 / 0	<user-defined> OFF	not pre-allocated	-
10 / 1	<user-defined> ON		
10 / 2	<user-defined> OFF	not pre-allocated	-
10 / 3	<user-defined> ON		

7.2.1.2 Single-point indications

- Single-point indications can be routed on these positions as “Destination system interface” using the **DIGSI Configuration matrix**.

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
10 / 4	<user-defined>	not pre-allocated	-
10 / 5	<user-defined>	not pre-allocated	-
10 / 6	<user-defined>	not pre-allocated	-
10 / 7	<user-defined>	not pre-allocated	-
11 / 0	<user-defined>	not pre-allocated	-
11 / 1	<user-defined>	not pre-allocated	-
11 / 2	<user-defined>	not pre-allocated	-
11 / 3	<user-defined>	not pre-allocated	-
11 / 4	<user-defined>	not pre-allocated	-
11 / 5	<user-defined>	not pre-allocated	-
11 / 6	<user-defined>	not pre-allocated	-
11 / 7	<user-defined>	not pre-allocated	-
12 / 0	<user-defined>	not pre-allocated	-

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
12 / 1	<user-defined>	not pre-allocated	-
12 / 2	<user-defined>	not pre-allocated	-
12 / 3	<user-defined>	not pre-allocated	-
12 / 4	<user-defined>	not pre-allocated	-
12 / 5	<user-defined>	not pre-allocated	-
12 / 6	<user-defined>	not pre-allocated	-
12 / 7	<user-defined>	not pre-allocated	-
13 / 0	<user-defined>	not pre-allocated	-
13 / 1	<user-defined>	not pre-allocated	-
13 / 2	<user-defined>	not pre-allocated	-
13 / 3	<user-defined>	not pre-allocated	-
13 / 4	<user-defined>	not pre-allocated	-
13 / 5	<user-defined>	not pre-allocated	-
13 / 6	<user-defined>	not pre-allocated	-
13 / 7	<user-defined>	not pre-allocated	-
14 / 0	<user-defined>	not pre-allocated	-
14 / 1	<user-defined>	not pre-allocated	-
14 / 2	<user-defined>	not pre-allocated	-
14 / 3	<user-defined>	not pre-allocated	-
14 / 4	<user-defined>	not pre-allocated	-
14 / 5	<user-defined>	not pre-allocated	-
14 / 6	<user-defined>	not pre-allocated	-
14 / 7	<user-defined>	not pre-allocated	-
15 / 0	<user-defined>	not pre-allocated	-
15 / 1	<user-defined>	not pre-allocated	-
15 / 2	<user-defined>	not pre-allocated	-
15 / 3	<user-defined>	not pre-allocated	-
15 / 4	<user-defined>	not pre-allocated	-
15 / 5	<user-defined>	not pre-allocated	-
15 / 6	<user-defined>	not pre-allocated	-
15 / 7	<user-defined>	not pre-allocated	-
16 / 0	<user-defined>	not pre-allocated	-
16 / 1	<user-defined>	not pre-allocated	-
16 / 2	<user-defined>	not pre-allocated	-
16 / 3	<user-defined>	not pre-allocated	-
16 / 4	<user-defined>	not pre-allocated	-
16 / 5	<user-defined>	not pre-allocated	-
16 / 6	<user-defined>	not pre-allocated	-

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
16 / 7	<user-defined>	not pre-allocated	-
17 / 0	<user-defined>	not pre-allocated	-
17 / 1	<user-defined>	not pre-allocated	-
17 / 2	<user-defined>	not pre-allocated	-
17 / 3	<user-defined>	not pre-allocated	-
17 / 4	<user-defined>	not pre-allocated	-
17 / 5	<user-defined>	not pre-allocated	-
17 / 6	<user-defined>	not pre-allocated	-
17 / 7	<user-defined>	not pre-allocated	-
18 / 0	<user-defined>	not pre-allocated	-
18 / 1	<user-defined>	not pre-allocated	-
18 / 2	<user-defined>	not pre-allocated	-
18 / 3	<user-defined>	not pre-allocated	-
18 / 4	<user-defined>	not pre-allocated	-
18 / 5	<user-defined>	not pre-allocated	-
18 / 6	<user-defined>	not pre-allocated	-
18 / 7	<user-defined>	not pre-allocated	-
19 / 0	<user-defined>	not pre-allocated	-
19 / 1	<user-defined>	not pre-allocated	-
19 / 2	<user-defined>	not pre-allocated	-
19 / 3	<user-defined>	not pre-allocated	-
19 / 4	<user-defined>	not pre-allocated	-
19 / 5	<user-defined>	not pre-allocated	-
19 / 6	<user-defined>	not pre-allocated	-
19 / 7	<user-defined>	not pre-allocated	-
20 / 0	<user-defined>	not pre-allocated	-
20 / 1	<user-defined>	not pre-allocated	-
20 / 2	<user-defined>	not pre-allocated	-
20 / 3	<user-defined>	not pre-allocated	-
20 / 4	<user-defined>	not pre-allocated	-
20 / 5	<user-defined>	not pre-allocated	-
20 / 6	<user-defined>	not pre-allocated	-
20 / 7	<user-defined>	not pre-allocated	-
21 / 0	<user-defined>	not pre-allocated	-
21 / 1	<user-defined>	not pre-allocated	-
21 / 2	<user-defined>	not pre-allocated	-

7.2.1.3 Diagnosis

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
21 / 3	Device OK	1 = Update of the device replica in the SIPROTEC device completed after initial start or restart	51
21 / 4	Settings Calc.	1 = Settings calculation is running	70
21 / 5	Error Sum Alarm	1 = Error with a summary alarm ON	140
21 / 6	Alarm Sum Event	1 = Alarm summary event ON	160
21 / 7	Data valid	1 = Data in the PROFIBUS-DP message are valid. (This indication is created by the PROFIBUS-DP slave; not available in DIGSI and not relocatable.)	-

7.2.2 Event list

- Information regarding the handshake bytes as well as the retrieval methods of the event list via PROFIBUS-DP can be found in the manual "SIPROTEC Communication module, PROFIBUS-DP - Communication profile".

Offset	Designation of the SIPROTEC objects	Comments	Internal object no.
22	Control_I	Handshake byte for event list via PROFIBUS-DP	-
23	SPARE	reserved for future use (the value 0 is transmitted at this position)	-
24	Message block #1	Identification #1	-
25		Value #1	
26		Time stamp #1	
33			
34	Message block #2	Identification #2	-
35		Value #2	
36		Time stamp #2	
43			
44	Message block #3	Identification #3	-
45		Value #3	
46		Time stamp #3	
53			

Glossary

CFC	Continuous Function Chart
DC	Double command
DDB file / GSD file	<p>The DDB file contains the Device Data Base (technical characteristics) of the PROFIBUS-DP communication module (PROFIBUS-DP slave).</p> <p>This file is required for configuration of the PROFIBUS-DP master and is supplied together with DIGSI.</p>
DIGSI	Parameterization system / parameterization software for SIPROTEC devices
DP	Double-point indication
Input data / Input direction	Data from the PROFIBUS-DP slave to the PROFIBUS-DP master.
Octet	Term from EN 50170, one octet corresponds to 8 bits.
OLM	Optical Link Module
Output data / Output direction	Data from the PROFIBUS-DP master to the PROFIBUS-DP slave.
PNO	PROFIBUS Nutzerorganisation (PROFIBUS International Organization)
PROFIBUS-DP	PROFIBUS - Decentralized Peripherals
PSE	PROFIBUS interface module with (electrical) isolated RS485 interface for the SIPROTEC devices from Siemens.
PSO	PROFIBUS interface module with fibre-optical interface for the SIPROTEC devices from Siemens.
SC	Single command
SP	Single-point indication

Index

A

Annunciations 17

C

Configuration data 18

D

Double commands 24, 30, 36, 44, 54, 66

Double-point indications 26, 32, 39, 47, 59, 71

E

Event list

 Handshake byte in input direction ... 34, 51, 76

 Handshake byte in output direction . 30, 44, 66

 Message blocks 34, 51, 76

M

Measured values 42, 50

P

PROFIBUS-DP

 Configuration data 18

 Configuration in the master system 20

 Event list 34, 51, 76

Q

Qualified personnel (definition) 5

S

Single commands 24, 30, 37, 45, 55, 68

Single-point indications 26, 32, 40, 48, 61, 73

T

Target audience 4

Typographic conventions 5

V

Validity of the manual 4

